



MET ONE 7000 Series Remote Airborne Particle Counters

Highest accuracy non-viable particle monitoring for EC/FDA compliance

MET ONE 7000 SERIES
REMOTE AIRBORNE PARTICLE COUNTERS

The MET ONE 7000 remote the most accurate counter and sterile pharm

Enhanced accuracy

*ISO 21501 certified calibration
provides data accuracy and repeatability*

Built-in user notification

*For particle monitoring events
enables instant troubleshooting*

System integration

*Integrates to any FMS system
with flexible communication options*



Remote airborne particle counters provide continuous monitoring for the aseptic pharmaceutical production environments



Protected sensor

VHP tolerant optics, washdown resistant enclosure protects from accidental exposure to harmful disinfecting chemicals

Lowest cost of ownership

Proven reliable Long Life Laser™ diode

Reduced calibration time

Quick connect feature reduces time and cost of routine calibration

MET ONE 7000 remote particle counters are designed using patented technology to comply with new ISO 21501 calibration requirements that ensure measuring 0.3 μm to 10.0 μm particles with accuracy and repeatability. With flexible communication and OPC server options, the MET ONE 7000 easily integrates to any Facility Monitoring System. Built-in indication lights notify users of particle events such as reaching an alarm or alert level, eliminating the need to install additional hardware in the sterile environment.

Specially selected optical component materials and effectively sealed 316L stainless-steel enclosure make the MET ONE 7000 tolerant to typical VHP based disinfecting cycles and washdown processes used in cleanrooms. Features such as DIP switches for address setting, quick-connect cables and tubing reduce instrument removal and reinstallation time during routine calibration and maintenance work. Built with Long Life Laser™ technology and supported by dependable after sales support from Hach, the MET ONE 7000 minimizes cost of ownership and offers unparalleled user experience in product quality and reliability.

Specifications

<i>Light Source</i>	Long Life Laser™ diode
<i>Weight</i>	AC version: 3.96 kg (8.7 lbs) DC version: 3.91 kg (8.6 lbs)
<i>Dimensions Enclosure</i>	22.9 W x 12.5 D x 16.0 H cm (9.02 x 4.92 x 6.3 inches) 316L stainless-steel sealed enclosure with sealed connectors suitable for washdown area
<i>Status Indicator</i>	Multi-colored LED for normal status, count alarm, count alert, sensor failure, flow failure or communication failure
<i>Power Requirements</i>	24 VDC ±10% or 100 to 230 VAC 50/60 Hz
<i>Power Consumption</i>	Ethernet unit: 6.9 W for DC, 8.9 W for AC maximum Serial unit: 5.9 W for DC, 7.6 W for AC maximum Analog unit: 6.1 W for DC, 7.9 W for AC maximum Wireless unit: 9.7 W DC, 12.5 W AC maximum
<i>Operating Temperature</i>	10 to 32 °C (50 to 90 °F), 5 to 95% relative humidity, non-condensing
<i>Storage Temperature</i>	-40 to 70 °C (-40 to 158 °F), 5 to 98% relative humidity, non-condensing
<i>Signal Output Options</i>	Ethernet or Wireless with TCP/IP protocol Serial RS-485 with Modbus RTU or FXB communication protocol Analog 4–20 mA
<i>Vacuum Requirements</i>	At least 40.6 cm (16 inches) Hg
<i>Number of Size Channels</i>	Standard 2 or Optional 4
<i>Flow Control</i>	Through critical orifice
<i>Isolation Valve</i>	Built-in solenoid valve
<i>Coincidence Loss</i>	Model 7005: 5% at 2,000,000 particles/ft ³ (70,600,000 particles/m ³) Model 7015: 5% at 400, 000 particle/ft ³ (14,000,000 particles/m ³)
<i>False Count Rate</i>	One or less in five minutes
<i>Accessories Included</i>	Mounting Plate, Isokinetic Probe, Wall Plate, Connector Umbilical Cables and Tubing, Operator Manual
<i>How To Order</i>	20887_5-N_--_--_--

0 = DC Power Cord
 B = Type B AC Power Cord
 D = Type D AC Power Cord
 E = Type E AC Power Cord
 G = Type G AC Power Cord
 J = Type J AC Power Cord
 D = 24 VDC Input Power
 A = 100~230 VAC 50/60 HZ Input Power
 A = Analog 4~20 mA
 E = Ethernet
 S = Serial RS-485
 W = Wireless*
 F = With Flow Measurement
 N = Without Flow Measurement
 N = No Built-in Pump
 5 = 0.5 µm Minimum Sensitivity
 0 = 0.1 CFM
 1 = 1.0 CFM

Optional Accessories

Optional 4-Channel Setting
 Purge Filters, 1.0 CFM 1/4 Tube and 0.1 CFM 1/8 Tube
 Isokinetic Probes, 0.1 CFM and 1.0 CFM
 Cable, Service Port Connector with RS-232 Converter
 Relative Humidity/Temperature Probe
 Brackets, for RH/Temp Probe and LED Indicator Stack/Isokinetic Probe
 Remote Indicator Light Assembly
 Cable Assembly, 3 m for Remote Indicator Light Assembly
 Power Supply Unit, 24 VDC @ 5.0 A, Universal Input for FMS

For a comprehensive parts and accessories list, please refer to the user manual.
 * Wireless option is available in limited number of countries. Please contact your Hach sales representative.

Beckman Coulter Life Sciences
 250 S Kraemer Blvd
 Brea, CA 92821 USA
 Telephone: 800-866-7889
 E-mail: insidesalesgp@beckman.com
www.particle.com



Lit. No. 5237
G9 Printed in USA

© Beckman Coulter Life Sciences 2013. All rights reserved.

In the interest of improving and updating its equipment, Beckman Coulter reserves the right to alter specifications to equipment at any time.

CLASS 1 LASER PRODUCT

Contact manufacturer for complete compliance details



Life Sciences