



### Intrinsically Safe Fixed Gas Detector For continuous monitoring of oxygen deficiency



#### Small. Durable. Reliable.

- Suitable for use in Zones 1 and 2 hazardous areas
- Industry standard 4-20mA output
- Plug-in replaceable electrochemical sensors
- Local LCD display
- Two wire connection, loop powered

#### Description

The Model MGT3 oxygen detectors provide reliable performance for workplace safety applications. Using electrochemical sensor technology to detect for oxygen deficiency in the atmosphere, these intrinsically safe detectors are designed to be incapable of producing heat or spark sufficient to ignite an explosive atmosphere.

The industry standard 4-20mA current loop is used to power the detector and to convey the detected gas levels to a controller. This means that under zero gas conditions 4mA is drawn from the supply, and under full scale gas conditions 20mA is drawn from the supply. The current varies linearly for gas levels between zero and full scale.

Safety barriers must be used to connect the power and signals between the gas detector and the safe area. This is required to preserve the safety integrity of the installation by limiting the power entering the potentially explosive area to a safe level.

A marine version of the MGT3 is available. This version is housed in a cast aluminum enclosure to provide higher RFI immunity where high power portable radios are used in the close confines of a vessel. The enclosure is plated and painted to withstand the harsh salt spray environment of the marine industry. The digital display is fitted with a sliding stainless steel front cover designed to remain closed over the display window when not being viewed. This maintains the RFI shielding properties of the enclosure during normal operation.



#### Hazardous Area Certification

Certificate number:	BAS 01ATEX2300 Code II 2G Ex ia IIC T4 Gb (-20°C < Ta < +60°C)
Standard:	EN 60079-0: 2009 EN 60079-1: 2007 EN 60079-11: 2007
Zones:	0, 1, & 2

An optional weather guard is available for installations exposed to the atmosphere or contaminants and for use in wash down areas. The weather guard improves the reliability of the gas detector in harsh environments by reducing the possibility that water or other contaminants will enter the sensor. The weather guard is attached with tamperproof screws.

# MODEL MGT3-O2

## Intrinsically Safe Fixed Gas Detector

### Specifications

Material	Standard housing: composite (ABS and polycarbonate) Marine version: cast aluminum alloy
Cable entry	1 x M20 or ½" NPT
Dimensions	122 x 122 x 75mm (4.8 x 4.8 x 3.0in)
Weights	Standard housing (excluding weatherguard) – 660 grams (1.5 lbs.) Marine version (excluding weatherguard) – 1 kg (2.2 lbs.) Weatherguard – 225 grams (0.5 lbs.)
Display	LCD
Gas types	Oxygen and toxic gases
Supply voltage	7 to 30VDC (for 4 to 20mA signal)
Output signal	0mA – open circuit 2mA – fault 4mA – zero gas 20mA – full scale gas 22mA – over-range
Max. cable loop resistance	Signal – 560 ohms at 24VDC
Sensor type	Electrochemical
Measurement range	0-21% O <sub>2</sub>
Response time	Sensor response times vary according to the sensor type
IP rating	Enclosure: IP66 Sensor: IP65
Operating temperature	Varies with the sensor type, typically -20 to +40°C (-4°F to +104°F)
Storage temperature	-20 to +50°C (-4°F to +122°F)
Humidity range, oxygen	0 to 99% RH non-condensing
Humidity range, toxic	15 to 95% RH non-condensing
Operating pressure	Atmospheric (± 10%)

Specifications are subject to change without notice.

### Order Information

Part No.	Description	Stock No.
2-06-2002-58-0	MGT3 oxygen detector, range 0-21% oxygen	SS401
2-06-2002-46-1	Protective weather guard	SS475



**Neutronics  
Gas Analysis Solutions**  
456 Creamery Way  
Exton, PA 19341

Tel: 610.524.8800  
Fax: 610.524.8807  
Email: info@neutronicsinc.com

[www.analyzegas.com](http://www.analyzegas.com)

